


Double Seal Brass Glands - Metric & Pg Thread

Double seal glands provide a wide range of cable clamping for each size, as the internal layer of the “onion-skin” seal can be removed easily. Upon request, these glands can be supplied with seal made of heat-resistant silicone (permanent temperature -40 to 300°C). For a replacement cap add ‘-C’ to the part number and for a replacement inner seal add ‘-IS’.

Features and specifications:

- **Operating Temperature:** -20 to 100°C (permanent),
-40 to 300°C (intermittent, with silicone seal)
- **Ingress Protection:** IP68 @ 5 bar
- **Material:** Body and dome: Brass, nickel plated; Seal: Chloroprene;
O-ring: NBR



Brass Metric Double Seal Glands (Order by Part No.)

M	Part No.	Range(double seal)		Range (single seal)		Gland Dimensions				Pack
		mm	Inches	mm	Inches	TD	TL	H	SW	
M12x1.5	180.812	–	–	4.0-6.0	0.157-0.236	12	6.0	18.0	14	50
M16x1.5	180.817	4-6	0.157-0.236	6.5-9.0	0.256-0.354	16	5.1	23.9	18	50
M20x1.5	180.820	4.5-7	0.177-0.276	7.0-12	0.276-0.472	20	6.0	21.5	22	50
M25x1.5	180.825	10-13	0.394-0.512	14-17.5	0.551-0.689	25	7.0	22.5	28	25
M32x1.5	180.832	14.5-18	0.571-0.709	19-23.5	0.748-0.925	32	8.0	26.0	35	25
M40x1.5	180.840	16.5-23.5	0.650-0.925	19.5-27	0.768-1.063	40	8.0	35.5	43	10

Information subject to change without notice - All dimensions in mm except where indicated.

Brass Pg Double Seal Glands (Order by Part No.)

Pg	Part No.	Range(double seal)		Range (single seal)		Gland Dimensions				Pack
		mm	Inches	mm	Inches	TD	TL	H	SW	
Pg7	180.807	–	–	4-7	0.157-0.276	12.5	6.0	18.0	15	50
Pg9	180.809	4-6	0.157-.0236	6-10	0.236-0.394	15.2	6.0	18.7	18	50
Pg11	180.811	5-7	0.197-0.276	7-12	0.276-0.472	18.6	6.0	20.5	22	50
Pg13.5	180.813	8-10	0.315-0.394	10-15	0.394-0.591	20.4	6.0	21.0	24	50
Pg16	180.816	8-10	0.315-0.394	10-15	0.394-0.591	22.5	6.0	21.0	24/25	25
Pg21	180.821	10-13	0.394-0.512	13-20	0.512-0.787	28.3	7.6	25.0	32	25
Pg29	180.829	19-21	0.748-0.827	21-28	0.827-1.102	37.0	8.0	25.5	40	20
Pg29	180.830	19-21	0.748-0.827	21-28	0.827-1.102	37.0	16.0	25.5	40	20
Pg36	180.836	26-30	1.024-1.181	30-35	1.18-1.378	47.0	8.0	28.3	50	15
Pg42	180.842	35-39	1.378-1.535	39-44	1.535-1.732	54.0	10.0	32.2	58	12
Pg48	180.848	37-40	1.457-1.575	40-48	1.575-1.890	59.3	11.0	34.1	64	12

Information subject to change without notice - All dimensions in mm except where indicated.