

# Solderless Crimp Terminal Kits

ITC's most common vinyl-insulated crimp terminals are now also supplied in a sturdy and practical metal case, with an optional crimping tool. Convenient for any electrical shop, and a great solution for use on a truck or van. Case dimensions: 345x260x45mm (1x2x2.4")








## Solderless Crimp Terminal Kits (Order by Part No.)

Range AWG / mm <sup>2</sup>	Part No.	Content	Contents Qty	Tool
22 – 10AWG 0.50 – 6.0mm <sup>2</sup>	199.141K	20 types of ring, spade, disconnect insulated crimp terminals, butt splices and closed-end connectors; 22-10AWG	500 pieces	–
	199.142K		500 pieces	500.821 504.921*

\* alternate tool; Information subject to change without notice

## Kit contents

Range AWG mm <sup>2</sup>	Stud Size	Part No.	Description		Qty	
22 – 16AWG 0.5 – 1.5mm <sup>2</sup>	4.3mm, #8	311.014	Insulated ring terminal		25	
	5.3mm, #10	311.015	Insulated ring terminal		25	
16 – 14AWG 1.5 – 2.5mm <sup>2</sup>	10.4mm, 3/8"	311.028	Insulated ring terminal		25	
12 – 10AWG 4.0 – 6.0mm <sup>2</sup>	4.3mm, #8	311.034	Insulated ring terminal		25	
16 – 14AWG 1.5 – 2.5mm <sup>2</sup>	3.7mm, #6	311.023	Insulated ring terminal		25	
12 – 10AWG 4.0 – 6.0mm <sup>2</sup>	5.3mm, #10	311.035	Insulated ring terminal		25	
16 – 14AWG 1.5 – 2.5mm <sup>2</sup>	4.3mm, #8	311.024	Insulated ring terminal		25	
12 – 10AWG 4.0 – 6.0mm <sup>2</sup>	10.4mm, 3/8"	311.038	Insulated ring terminal		25	
16 – 14AWG 1.5 – 2.5mm <sup>2</sup>	5.3mm, #10	311.025	Insulated ring terminal		25	
22 – 16AWG 0.5 – 1.5mm <sup>2</sup>	5.3mm, #10	312.015	Insulated spade terminal			25
16 – 14AWG 1.5 – 2.5mm <sup>2</sup>	5.3mm, #10	312.025	Insulated spade terminal			25
12 – 10AWG 4.0 – 6.0mm <sup>2</sup>	5.3mm, #10	312.035	Insulated spade terminal			25
Range	Tab Size	Part No.	Description			Qty
22 – 16AWG 0.5 – 1.5mm <sup>2</sup>	.250x.032"	314.015	Insulated female disconnect			25
16 – 14AWG 1.5 – 2.5mm <sup>2</sup>	.250x.032"	314.025	Insulated female disconnect			25
12 – 10AWG 4.0 – 6.0mm <sup>2</sup>	.250x.032"	314.035	Insulated female disconnect			25
Range		Part No.	Description		Qty	
22 – 16AWG 0.5 – 1.5mm <sup>2</sup>	–	316.310	Insulated butt splice		25	
16 – 14AWG 1.5 – 2.5mm <sup>2</sup>	–	316.320	Insulated butt splice		25	
12 – 10AWG 4.0 – 6.0mm <sup>2</sup>	–	316.330	Insulated butt splice		25	
16 – 14AWG 1.5 – 2.5mm <sup>2</sup>	–	326.820	Close end crimp connector, round tip		25	
12 – 10AWG 4.0 – 6.0mm <sup>2</sup>	–	326.830	Close end crimp connector, round tip		25	
–	–	500.821*	Crimping Tool - Series 800 for insulated crimp terminals 22-10AWG		1	

\* for 199.142K kit only. Information subject to change without notice

## Solderless Crimp Terminal Slide-Box Kits

ITC's Solderless Crimp Terminals are also available in handy, attractive packages - convenient for display and for usage in electrical shops of any size.

The plastic slide-box box is fully reusable.

### Features and specifications:

- Box made of impact-resistant thermoplastic resin, designed to hang on standard display hooks. Covers are in transparent plastic, to show contents of each compartment
- Covers slide easily with thumb action, yet single compartments are safely closed until needed
- Available in prepared kits or as required - consult ITC
- The empty slide-box is also available in eight different colours - see page 26



### 'Slide-Box' Kits (Order by Part. No.)

Range AWG mm <sup>2</sup>	Part No.	Description	Compartment 1	Compartment 2	Compartment 3	Compartment 4	Compartment 5
22 – 16 0.5 – 1.5	790.120	RED Crimp terminal assortment kit	50 non insulated ring terminals #8	50 insulated ring terminals #8	50 insulated spade term #8	25 insulated butt splices, 22-16AWG	25 fully insulated disconnects ¼"
16 – 14 1.5 – 2.5	790.121	BLUE Crimp terminal assortment kit	50 non insulated ring terminals #10	40 insulated ring terminals #10	40 insulated spade term #10	20 insulated butt splices, 16-14AWG	20 fully insulated disconnects ¼"
12 – 10 4.0 – 6.0	790.122	YELLOW Crimp terminal assortment kit	40 non insulated ring terminals #10	20 insulated ring terminals #10	20 insulated spade term #10	15 insulated butt splices, 12-10AWG	15 fully insulated disconnects ¼"

Information subject to change without notice

